



**MITSUBISHI DIESEL ENGINE
TECHNICAL INFORMATION**

ITEM NO.

T0216-0001E Rev.2 (1/4)

DATE

March, 2013

Specification Sheets of S16R-PTA Engine

Specification Sheets of S16R-PTA Engine are enclosed herein.

Revision	First Edition : September, 2007 (T13-0311-E Jun.99)	Engine Engineering Department Engine System Designing Section		
	Rev.1 : Dec., 2012			
	Rev.2 : Mar., 2013	Approved by	Checked by	Drawn by
		T.HASHIGUCHI	T.OGURA	K.NAKAMURA

GENERAL ENGINE DATA

Type	4-Cycle, Water Cooled	
Aspiration	Turbo-Charged, After Cooler (Jacket water to Cooler)	
Cylinder Arrangement	60°V	
No. of Cylinders	16	
Bore mm(in.)	170	(6.69)
Stroke mm(in.)	180	(7.09)
Displacement liter(in ³)	65.37	(3989)
Compression Ratio	14.0:1	
Dry Weight - Engine only - kg(lb)	6750	(14884)
Wet Weight - Engine only - kg(lb)	7127	(15715)

PERFORMANCE DATA

Steady State Speed Stability Band at any Constant Load		
Electric Governor - %	±0.25 or better	
Maximum Overspeed Capacity - rpm	2100	
Moment of inertia of Rotating Components - N·m ² (lbf·ft ²)	793	(1918)
(Includes Std. Flywheel)		
Cyclic Speed Variation with Flywheel at 1800rpm	1/283	
1500rpm	1/188	
1200rpm	1/131	

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Flywheel Housing - N·m(lbf·ft)	4413	(3256)
---	------	--------

AIR INLET SYSTEM

Maximum Intake Air Restriction (Includes piping)		
With Clean Filter Element - mm H ₂ O (in.H ₂ O)	400	(15.7)
With Dirty Filter Element - mm H ₂ O (in.H ₂ O)	635	(25.0)

EXHAUST SYSTEM

Maximum Allowable Back Pressure - mm H ₂ O (in.H ₂ O)	600	(23.6)
---	-----	--------

LUBRICATION SYSTEM

Oil Pressure at Idle - MPa(psi)	0.2~0.3	(29~43)
at Rate Speed - MPa(psi)	0.49~0.64	(71~93)
Maximum Oil Temperature of Oil pan - °C(°F)	110	(230)
Oil Capacity of Standard Oil pan High - liter (U.S.gal)	200	(52.8)
Low - liter (U.S.gal)	140	(37.0)
Total System Capacity (Includes Oil Filter) - liter (U.S.gal)	230	(60.8)
Maximum Angle of Installation (Std. Pan) Front Down	5°	
(Engine Only) Front Up	5°	
Side to Side	22.5°	

COOLING SYSTEM

Coolant Capacity (Engine only) - liter (U.S.gal)	170	(44.9)
Maximum External Friction Head at Engine Outlet - MPa(psi)	0.034	(5.0)
Maximum Static Head of Coolant above Crankshaft Center - m(ft)	10	(32.8)
Maximum Outlet Pressure of Engine Water Pump - MPa(psi)	0.20	(28.6)
Standard Thermostat (modulating) Range- °C(°F)	71~85	(160~185)
Maximum Coolant Temperature at Engine Outlet- °C(°F)	98	(208)
Minimum Coolant Expansion Space - % of System Capacity	10	
Maximum Coolant Temperature at Intercooler Inlet, TK type- °C(°F)	-	
Maximum Air Restriction on Discharge Side of Radiator and Fan-mm H ₂ O(in.H ₂ O)	10	(0.4)

The specifications are subject to change without notice.

APPLICATION : GENERATOR

Pub. No. T0216-0001E Rev.2 2/4

FUEL SYSTEM

Fuel Injector	Mitsubishi PS8 × 2
Maximum Suction Head of Feed Pump - mm Hg (in. Hg)	75 (3.0)
Maximum Static Head of Return & Leak Pipe - mm Hg (in.Hg)	150 (5.9)

STARTING SYSTEM

Battery Charging Alternator - V-Ah	24-30
Starting Motor Capacity - V -kW	24-7.5×2
Maximum Allowable Resistance of Cranking Circuit - m Ω	1.5
Recommended Minimum Battery Capacity	
At 5 °C(41°F) and above - Ah	300
Below 5 °C(41°F) through - 5 °C(23°F)	600

The specifications are subject to change without notice.

APPLICATION : GENERATOR

Pub. No. T0216-0001E Rev.2 3/4

ENGINE RATING

All data represent net performance with standard accessories such as air cleaner, inlet /exhaust manifolds, fuel oil system, L.O. pump, etc. under the condition of 100kPa(29.6inHg) barometric pressure, 77°F(25°C) ambient temperature and 30% relative humidity.

ITEM	UNIT	STAND-BY POWER			PRIME POWER			CONTINUOUS C	CONTINUOUS D
		60Hz	50Hz	60Hz	60Hz	50Hz	60Hz	50Hz	50Hz
Engine Speed	rpm	1800	1500	1200	1800	1500	1200	1500	1500
No. of Cylinders		16							
Bore	mm (in.)	170 (6.69)							
Stroke	mm (in.)	180 (7.09)							
Displacement	liter (in. ³)	65.37 (3989) THIS							
Brake Horse power without Fan	kW (HP)	1750 (2346)	1620 (2172)	1120 (1501)	1590 (2131)	1480 (1984)	1020 (1367)	1330 (1783)	1180 (1582)
Brake Mean Effective Pressure without Fan	MPa (psi)	1.8 (258)	2.0 (287)	1.7 (248)	1.6 (235)	1.8 (262)	1.6 (226)	1.6 (236)	1.4 (209)
Mean Piston Speed	m/s (ft/min)	10.8 (2126)	9.0 (1772)	7.2 (1417)	10.8 (2126)	9.0 (1772)	7.2 (1417)	9.0 (1772)	9.0 (1772)
Maximum Regenerative Power Absorption Capacity without Fan	kW (HP)	192 (258)	140 (188)	96 (129)	192 (258)	140 (188)	96 (129)	140 (188)	140 (188)
Intake Air flow	m ³ /min (CFM)	141 (4979)	128 (4520)	90 (3178)	127 (4484)	117 (4131)	82 (2895)	107 (3778)	96 (3390)
Exhaust Gas Flow	m ³ /min (CFM)	373 (13171)	339 (11970)	237 (8368)	337 (11899)	309 (10911)	216 (7627)	284 (10028)	253 (8933)
Coolant Flow	liter/min (U.S. GPM)	1850 (489)	1650 (436)	1300 (343)	1850 (489)	1650 (436)	1300 (343)	1650 (436)	1650 (436)
Coolant Flow to Intercooler (TK only)	liter/min (U.S. GPM)	—	—	—	—	—	—	—	—
Cooling Air Flow (Std. Fan)	m ³ /min (CFM)	1950 (68855)	1950 (68855)	1560 (55084)	1950 (68855)	1950 (68855)	1560 (55084)	1950 (68855)	1950 (68855)
Fan Loss Horse Power (Std. Fan)	kW (HP)	50 (67)	30 (40)	20 (27)	50 (67)	30 (40)	20 (27)	30 (40)	30 (40)
Radiated Heat to Ambient	kJ/hr (BTU/min)	444750 (7027)	403417 (6374)	282634 (4466)	401261 (6340)	368498 (5822)	257402 (4067)	338017 (5341)	301939 (4771)
Heat Rejection to Coolant	kJ/hr (BTU/min)	3706247 (58558)	3361804 (53116)	2355280 (37213)	3343839 (52832)	3070819 (48518)	2145016 (33891)	2816811 (44505)	2516155 (39755)
Heat Rejection to Inter Cooler (TK Version)	kJ/hr (BTU/min)	—	—	—	—	—	—	—	—
Heat Rejection to Exhaust	kJ/hr (BTU/min)	4374807 (69121)	3850015 (60829)	2752910 (43495)	3908364 (61751)	3516772 (55564)	2507147 (39612)	3324929 (52533)	2998740 (47379)
Noise Level (1 m height & distance) (excludes, Intake, Exhaust & Fan)	dB(A)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

The specifications are subject to change without notice.

APPLICATION : GENERATOR

Pub. No. T0216-0001E Rev.2 4/4